



QUADRATHERM® Heater Spacing*

House Length	400 Feet (122 m)		500 Feet (152.4 m)		600 Feet (182.9 m)	
House Width	40 to 50 Feet (12.2-15.2 m)		40 to 50 Feet (12.2-15.2 m)		50 to 66 Feet (15.2-20.1 m)	
	Brood End	Non-Brood End	Brood End	Non-Brood End	Brood End ⁺	Non-Brood End
Distance from End Wall and from Curtain	15 feet (4.6 m)	40 feet (12.1 m)	15 feet (4.6 m)	35 feet (10.7 m)	15 feet (4.6 m)	30 feet (9.1 m)
Distance between Heaters	34 feet (10.4 m)	60 feet (18.3 m)	37 feet (11.3 m)	60 feet (18.3 m)	49 feet (14.9 m)	40 feet (12.1 m)

*Contact Chore-Time's Customer Service Department for a pipe size layout and drawing specific to your houses. Layouts may vary depending on house style, size and climate. Stir fans, inlets and tunnel doors should not blow directly on the heaters. Position units so there is no direct air movement on them during operation.

+Two rows of heaters.

	QuadRadiant® Heat Advantages vs. Tube Heat	QuadRadiant® Heat Advantages vs. Brooders	Brooder Heat Advantages vs. Tube Heat
More Even Heat Pattern	Yes	Yes	-
More Efficient Fuel Conversion	Yes	Yes	-
Rectangular Heat Profile	Yes	Yes	-
Flexible for Various House Widths	Yes	-	Yes
Winchable	Yes	-	Yes
Quicker Up-To-Temperature	Yes	Yes	Yes
No Air Intakes or Ducting	Yes	-	Yes
Easy to Move Units	Yes	-	Yes
Easily Accessible	Yes	-	Yes
Run Without Electricity**	Yes	-	Yes
Requires Fewer Units	-	Yes	-

**Low-Pressure, Snap-Action Model Only