



Space Heater Specifications

| Unit Name | DURA-THERM™ 250 | DURA-THERM™ |
|--|---|--|
| Heating area per unit | 2,750-4400 ft ² (255.5-408.8 m ²) | 2,500-4,000 ft ² (232.3-371.6 m ²) |
| Capacity (Maximum Per Hour) | | |
| Direct Spark or Hot Surface Ignition | 250,000 BTU (73.27 KwHr) LP or Nat. Gas | 225,000 BTU (65.94 KwHr) - LP |
| | | 200,000 BTU (58.6 KwHr) - Nat. Gas |
| Gas Consumption (Maximum) - LP | | |
| Direct Spark or Hot Surface Ignition | 2.73 gph (10.33 l/h) | 2.46 gph (9.31 l/h) |
| Gas Consumption (Maximum) - Natural Gas | | |
| Direct Spark or Hot Surface Ignition | 235.85 cfh (6.68 m ³ /h) | 213.8 cfh (6.05 m ³ /h) |
| Gas Pressure Requirements (Measured at Inlet) | | |
| LP | 11" WC (27.5 mbar) | 11" WC (27.5 mbar) |
| Natural Gas | 7" WC (17.5 mbar) | 7" WC (17.5 mbar) |
| Heater Size and Weight | | |
| Weight Per Complete Unit | 125 lbs. (56.7 kg) | 125 lbs. (56.7 kg) |
| Height x Length x Width | 30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm) | 30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm) |
| Minimum Clearance to Combustibles | | |
| Above, Below and Beside Unit | 20 in. (50.8 cm) | 20 in. (50.8 cm) |
| Exhaust Outlet | 120 in. (304.8 cm) | 120 in. (304.8 cm) |
| Electrical Requirements: 120 VAC (220/240 VAC, 50 or 60 Hz) | | |

The policy of Chore-Time is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use. Gas pipe layout assistance available to customers through authorized distributors. CSA (Canadian Standards Association) approved models are available. All models meet stringent standards for low carbon monoxide.